

# cast iron **CENTRIFUGAL PUMPS**

**Flotec**<sup>®</sup>

*Economical, general purpose centrifugal pumps can be used for water transfer, circulation, fountains, waterfalls, pressure boosting and sprinkling. Discharge can be rotated to horizontal or vertical installations.*

## FEATURES

- Capacities to 68 gallons per minute
- Ready-to-install 230 Volt motor -- see manual for 115 Volt conversion
- Heavy-duty motor
- Rugged, heavy-duty cast iron pump housing

**FP5552**

**2 HP**

Good 1 year warranty

**FP5542**

**1-1/2 HP**

Good 1 year warranty

**FP5532**

**1 HP**

Good 1 year warranty

**FP5522**

**3/4 HP**

Good 1 year warranty

**FP5512**

**1/2 HP**

Good 1 year warranty



## PERFORMANCE INFORMATION

Rating	Model	HP	Motor Voltage	NPT Pipe Size		Discharge Pressure PSI (Pounds per Square Inch)							Maximum PSI
				Suction	Discharge	25	30	35	40	45	50	55	
Good	FP5552	2	115/230	1-1/2"	1-1/4"	68	62	54	48	38	29	7	57
Good	FP5542	1-1/2	115/230	1-1/4"	1"	59	52	47	40	30	15	-	51
Good	FP5532	1	115/230	1-1/4"	1"	47	40	35	29	17	-	-	49
Good	FP5522	3/4	115/230	1-1/4"	1"	31	25	21	13	-	-	-	43
Good	FP5512	1/2	115/230	1-1/4"	1"	22	13	2	-	-	-	-	36

\*All performances shown in gallons per minute.